



## Jade Oil

- Displaces residual moisture and humidity from metal surfaces
- Helps to reduce tarnishing
- Can be used before waxing, oiling or painting
- Leaves a thin invisible film on the surface
- Use to fix Haematite and Antiquing Fluid



### USAGE

Interior

### COVERAGE

1 L  
16-20 m<sup>2</sup>

### APPLICATION

Cloth, brush  
or spray

### DRYING TIME

Minimum  
24 hours

### TOOL CLEANING

White Spirit

### Product use

Liberon Jade Oil displaces moisture from the surface of metals. It is ideal to 'dry' metals after using Liberon Antiquing Fluid or Haematite Cold Patinating fluid. Jade Oil will also help retard tarnishing after polishing by depositing a thin protective film on the surface of the metal.

### Preparation

Dry the surface of the metal with a soft cloth.

### Application

Wipe a soft cloth/cotton wool soaked in Jade Oil over the whole surface, or apply with a spray. Allow to dry for 24 hours without handling.

Metals to be handled frequently after using Jade Oil may be treated with Black Bison Wax or Liberon Finishing Oil for extra protection.

**Important:** Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

### Packaging

Jade Oil is available in 500 ml containers.

### Health and Safety

Flammable. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Keep out of the reach of children. Do not breathe vapour. Avoid contact with skin. Do not empty into drains. Use only in well-ventilated areas. If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.