



Hardwearing Floor Gel

- Resistant to heel impact and wear and tear
- Non-drip formula
- Ideal for stairs and balustrades
- Quick drying and odourless
- May be mixed with Liberon Wood Floor Dyes



| | | | | |
|--------------------------|---|-----------------------------|--|-------------------------------|
| USAGE Interior | COVERAGE 750 ml 10-12 m ² | APPLICATION Brush | DRYING TIME Min 2 hours between coats 24 hours final coat | TOOL CLEANING Water |
|--------------------------|---|-----------------------------|--|-------------------------------|

Hardwearing Floor Gel is a durable and long lasting varnish that is ideal for use on soft or hardwood flooring. The quick drying, non-drip formula makes it ideal for use on stairs and other upright areas such as balustrade.

Preparation

Sand the floor if required and remove all previous finishes. Ensure the surface is clean, dry and dust free. Hardwearing Floor Gel is designed for use on bare wood, however if you want to colour the wood you can apply Liberon Wood Floor Dye to the timber before varnishing. Alternatively Liberon Wood Floor Dye may be added to the varnish to create unique colour tones. Add one 250 ml Liberon Wood Floor Dye to one 2.5 L tin of Hardwearing Floor Gel. Liberon Wood Floor Dye is available in a range of wood shades.

Application

Stir well before use. Apply a reasonable coat of varnish evenly using a brush and allow to dry for a minimum of 2 hours before applying further coats. We recommend a minimum of 3 coats are applied, sanding lightly between coats if required. More coats may be required for heavy traffic areas. Allow the final coat of varnish a minimum of 24 hours drying time before using the floor.

Important: Always test product on a spare surface or inconspicuous area for colour compatibility and end result. This product may darken some woods.

Cleaning and maintenance

Wipe any spills immediately. For general maintenance wipe over with a damp mop or cloth using a mild detergent if required. If the surface shows signs of wear re-apply a coat of varnish or coat with Liberon Floor Reviver.

Precautions

- Allow all wood dyes to dry for a minimum of 8 hours before applying Hardwearing Floor Gel.
- Care must be taken on the application of the first coat of Hardwearing Floor Gel when being used over Liberon Wood Floor Dye. Keep brush strokes to a minimum as over brushing may lift out the colour.
- The varnish may raise the grain on some hard woods.
- Do not exceed a 10% dilution of Hardwearing Floor Gel with Liberon Wood Floor Dye (250 ml Dye to 2.5 L Varnish).

Ref: FL160106



- For a more durable finish we recommend Liberon Wood Floor Dye is only added to the varnish for the first coat and that subsequent coats are varnish only.

Health and Safety

Keep out of the reach of children. Do not empty into drains. Use only in well ventilated areas. Do not allow to freeze.

VOC information

EU limit value for Hardwearing Floor Gel (CatA/I): 140 g/L (2007) / 140 g/L (2010). Hardwearing Floor Gel contains Max 16 g/L VOC.

Liberon advice

Apply varnish on every other stair so as not to put the whole staircase out of use until it is dry. Ideal application conditions are between 12 and 25°C.

Packaging

Liberon Hardwearing Floor Gel is available in 2.5 L containers

Finishes

Clear Satin